



Data Sheet

Call accountant is an intuitive web-based billing system that connects to the SMDR port of your switch. Call accountant is designed for small to mid-size businesses or large companies with remote sites and is available in rack mountable or fully hosted and managed configurations.

Chassis

Form Factor: Available as a Tower (not rackable) a rack mounted server, or as a fully hosted solution

Height: 17.6" H (44.8cm)

Width: 6.8" W (17.1cm)

Depth: 18.4" D (46.7cm)

Weight: ~ 39.0 lbs. (17.7kg)

Power

Single power supply (305W)

Graphics

Integrated graphics

Management

OS-based monitoring and Dell Server Assistant for PowerEdge SC Server

Environmental

Operating Temperature: 10° to 35°C (50° to 95°F)

Operating Relative Humidity: 20% to 80% (noncondensing) with a maximum humidity gradation of 10% per hour

Operating Maximum Vibration: 0.25 G at 3-200 Hz for 15 minutes

Operating Maximum Shock: One shock pulse in the positive z axis (one pulse on each side of the system) of 41 G for up to 2 ms

Operating Altitude: -15.2 to 3048 m (-50 to 10,000 ft.)

Storage Temperature: -40° to 65°C (-40° to 149°F)

Storage Relative Humidity: 5% to 95% (noncondensing)

Storage Maximum Vibration: 0.5 G at 3-200 Hz for 15 minutes

Storage Maximum Shock: Six consecutively executed shock pulses in the positive and negative x, y, and z axes (one pulse on each side of the system) of 71 G for up to 2 ms

Storage Altitude: -15.2 to 10,600 m (-50 to 35,000 ft.)

Regulatory

ACA (Australia/New Zealand) Class B

BSMI (Taiwan)

CCC (China) Class B

CE (Europe) Class B: EN 55022, EN55024, EN61000-3-2, EN61000-3-3

CSA (Canada)

FCC (U.S.) Class B

FCC/ICES-003 (Canada) Class B

IEC (Europe) EN60950, EN60950-1

IECEE (U.S.) EN60950-1

IRAM (Argentina)

GOST (Russia)

MIC - RRL (Korea) Class B

NEMKO (Norway) Class B: EN 55022, EN55024, EN61000-3-2, EN61000-3-3

NEMKO (Norway) Safety: EN60950-1

NOM NYCE (Mexico)

SABS (South Africa)

SASO (Saudi Arabia)

SII (Israel)

SPRING PSB (Singapore)

UL 60950 (U.S.)

TUV (Germany)

VCCI (Japan) Class B